



Guardian™ Forced Air Heaters



*The best value in high quality,
dependable poultry confinement heating.*

Backed by L.B. White's 40 years of agricultural heating experience, Guardian forced air heaters offer an efficient direct-fired design combined with a range of heat outputs, ignition configurations and installation options. All delivered with a commitment to service that's second to none.

Dependable, Economical Heat

The L.B. White Guardian's time proven direct-fired design provides consistent, dependable heat for poultry environments. To meet the unique needs of different poultry production facilities, the Guardian offers:

- Highly efficient, direct-fired design
- Choice of heating models
 - 250,000 Btu/h
 - 325,000 Btu/h
- Variable heat output
- Three ignition configurations
 - Hot Surface
 - Spark
 - Pilot Light
- Versatile indoor and outdoor installation options

In addition, all L.B. White Guardian heaters are certified to meet or exceed U.S. and Canadian CSA safety standards.

Advanced Service Saver™ Monitoring

Available on both Guardian 250 and 325 heaters, L.B. White's advanced Service Saver™ constantly monitors your heater's performance (so you don't have to). With its easy-to-see display, Service Saver

can save you time and money by pinpointing any potential interruptions quickly and accurately.

Reliable, Low Maintenance Design

Designed to deliver outstanding performance with either natural gas (NG) or propane (LP), the L.B. White Guardian also features high temperature protection, an air proving switch and a totally enclosed motor to assure safe, dependable operation. Factor in the Guardian's high quality, corrosion resistant components and solid case construction and your Guardian will provide years of worry-free performance in even the toughest poultry environments.

Knowledgeable, Friendly Technical & Customer Support



With over 50 years of heating experience and a full line of forced air and radiant heating solutions, only L.B. White offers you the product quality, technical expertise and knowledgeable customer support

you can count on to help you design the best heating solution for your needs.

For more information about how L.B. White Guardian forced air heaters can help you improve production and reduce costs, please contact your local L.B. White representative or contact us directly at **800-345-7200**.

Guardian 250
Guardian 325



Guardian™ Forced Air Heater Specifications

Model Numbers:

Guardian 250

Guardian 325

Btu/h Rating:		
Maximum Input	250,000	325,000
Minimum Input (variable from)	160,000	200,000
Heater Configuration:		
Hot Surface Ignition	Yes	Yes
Spark Ignition	Yes	–
Pilot Light Ignition	Yes	–
Fuel Consumption (max.):		
Liquid Propane Gas (lbs./hr.)	11.6	15.1
Natural Gas (cu. ft./hr.)	250	325
Heated Air Output (CFM):	1,050	1,700
Inlet Gas Supply Pressure:		
Propane min./max. (in.W.C.)	11.5 / 13.5	11.5 / 13.5
Natural Gas min./max. (in.W.C.)	7.0 / 13.5	7.0 / 13.5
Electrical Supply (Volts / Hz / Phase):	115 / 60 / 1	220 / 60 / 1
Amps (Starting / Cont. Oper.):		
Hot Surface Ignition	11.8 / 4.8	10.5 / 3.5
Spark Ignition	3.9 / 2.6	–
Pilot Light Ignition	4.5 / 4.5	–
Cabinet Material:	Galvanized Steel*	Galvanized Steel*
Dimensions (in.):		
Length	30.8	36.0
Width	18.3	22.0
Height	28.3	30.0
Net Weight (lbs.):	116	150
Shipping Weight (lbs.):	126	160
Chain Hanging Kit:	O	O
Air Diverter:	O	O
Second Stage Regulator:	O	O
Thermostat:	O	O
Sediment Trap:	S	S
Gas Hose (10ft.):	O	O
Installation Options:		
Indoor Mount	Yes	Yes
Outdoor Mount	Yes	Yes
CSA U.S./Canada Certification:	Yes	Yes

* Exclusive Tri-shield coating available. Tri-shield coating consists of 3 unique protective layers including: a non-corrosive hot-dipped galvanized steel, an oven-cured epoxy primer and a baked, thermosetting polyester.

S = Standard O = Optional



L.B. White Guardian Forced Air Heaters are certified by:



Quality heaters you can count on.

Your L.B. White Dealer:

W6636 L.B. White Rd., Onalaska, WI 54650

(800) 345-7200

(608) 783-5691

(608) 783-6115, fax

info@lbwhite.com

© 2002 L.B. White Co.
All rights reserved.
All specifications are subject
to change without notice.

F#4956.0902